

TARALAY MILLENIUM



TARALAY MILLENIUM COMPACT

TARALAY MILLENIUM COMPACT is a multilayered vinyl floor covering available in 2m wide sheet, with a group T wear rating. The product comprises a **1 mm thick coated wear layer, made of pure vinyl, coloured throughout its thickness (no transparent wear layer and no filler)**. Its complete thickness is 2 mm. It is reinforced with a fibre glass grid for a better dimensional stability. The construction of the product yields a 8dB sound insulation rating and a **resistance to indentation of 0.03 mm**. This flooring is protected by the surface treatment, **PROTECSOL® Mat**, with a minimum thickness of 13µm, ensuring easy maintenance and no required polish for the entire lifetime of the product.

It is composed of 50% mineral and inexhaustible materials. It does not contain any heavy metals or CMR 1&2 components and it is 100% compliant with REACH. The product emission rate of volatile organic compounds is <10 micrograms/m³ (TVOC after 28 days ISO 16000-6). It is 100% recyclable.

TARALAY MILLENIUM COMFORT

TARALAY MILLENIUM COMFORT is a multilayered vinyl floorcovering available in 2m wide sheet, with a group T wear rating. The product comprises a **1 mm thick coated wear layer, made of pure vinyl, coloured throughout its thickness (no transparent wear layer and no filler)**. Its complete thickness is 3.4 mm. It contains a Very High Density (VHD) foam backing and is reinforced with 2 fibre glass grids which yields a **17dB sound insulation** rating and a **resistance to indentation of 0.07 mm**. This flooring is protected by the surface treatment, **PROTECSOL® Mat**, with a minimum thickness of 13µm, ensuring easy maintenance and no required polish for the entire lifetime of the product.









It is composed of 50% mineral and inexhaustible materials. It does not contain any heavy metals or CMR 1&2 components and it is 100% compliant with REACH. The product emission rate of volatile organic compounds is <10 micrograms/m³ (TVOC after 28 days ISO 16000-6). It is 100% recyclable.



Rubber leaves indelible stains on vinyl floorings: do not use mats with rubber backing and replace tubular furniture feet with those made of PVC or polyamide. Place mats of sufficient length at entrances to reduce outside sources of dirt.

IMPORTANT: The information contained in this document is valid from 01/01/2021 and

is subject to change at any time without notice. In the context of constantly changing technology, our customers are responsible, prior to any use, for checking with us that this document is the version in force.

			TARALAY MILLENIUM COMPACT	TARALAY MILLENIUM COMFORT
DESCRIPTION				
Total thickness	EN ISO 24346	mm	2.00	3.40
	ASTM F386-02	inch	0.08	0.12
Wearlayer thickness	EN ISO 24340	mm	1.00	1.00
	ASTM F410-02	inch	0.039	0.039
Weight	EN ISO 23997	g/sq.m	2725	3385
		lbs/sq.ft	0.56	0.69
Width of sheet	EN ISO 24341	cm	200	200
		feet - inch	6'6"	6'6"
Length of sheet	EN ISO 24341	m	20	25
		feet - inch	66'	82'
CLASSIFICATION				
Norm / Product specification	-	-	EN ISO 10582	EN 651
European classification	EN ISO 10874	class	34-43	34-42
Fire rating	EN 13501-1	class	Bfl-s1	Cfl-s1
Static electrical propensity	EN 1815	kV	< 2	< 2
Slip resistance ⁽¹⁾	DIN 51 130	class	R10	R10
PERFORMANCES				
Wear resistance	EN 660.2	mm³	≤ 2.0	≤ 2.0
Wear group	-	group	T	T
Type binder content	EN ISO 10582	type	I	-
Dimensional stability	EN ISO 23999	%	≤ 0.40	≤ 0.40
Impact sound insulation	EN ISO 717-2	dB	8	17
Sonorité à la marche	NFS 31 074	dB	-	< 65
Residual indentation (requirement)	EN ISO 24343-1	mm	≤ 0.10	≤ 0.20
Residual indentation (average measured value)	-	mm	~ 0.03	≈ 0.07
Castor chair test (type W)	ISO 4918	-	OK	OK
Conductivité thermique	EN ISO 10456	W/(m.k)	0.25	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6	≥ 6
Surface treatment	-	-	PROTECSOL® Mat	PROTECSOL® Mat
Chemical products resistance ⁽²⁾	EN ISO 26987	-	OK	OK
Anti-bacterial activity [E. coli - S. aureus - MRSA] ⁽³⁾	ISO 22196	-	> 99% inhibits growth	> 99% inhibits growth
Antiviral activity [human coronavirus] after 2h ⁽³⁾	ISO 21702	-	> 99,3 % (virucidal activity)	> 99% inhibits growth
ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000-6	micrograms/m³	<10	<10
Certification	-	-	Floorscore®	Floorscore®
CE MARKING				
CE	EN 14041		   	   

(1) For lifetime sustainable wet resistance, please refer to Tarasafe ranges.
 (2) Regarding the resistance to chemicals, please download the corresponding leaflet from our website.
 (3) The implementation of an effective cleaning regime is the most important defence against infection.

Gerflor International
 Tel: +33 (0)4 74 05 40 00
 Fax: +33 (0)4 74 05 03 13
 e-mail: gerflorcontract@gerflor.com

TARALAY MILLENIUM: AN ECO-RESPONSIBLE CHOICE



COMPOSITION
 100% REACH
 FREE of formaldehyde
 FREE of heavy metals
 FREE of solvent



RECYCLABLE
 100%



INDOOR AIR QUALITY
 100 times better than norms requirements
 (TVOC <10 micrograms/m³ after 28 days)



LCA
 Eco-designed according to a product specific Life Cycle Analysis



WELLNESS
 Anti slip performance R10
 Comfort:
 Walking comfort <65dB
 Impact noise reduction -17dB

Gerflor®
 theflooringgroup